

# The **l3pdfmanagement** module

## Managing central PDF resources

### L<sup>A</sup>T<sub>E</sub>X PDF management bundle

The L<sup>A</sup>T<sub>E</sub>X Project\*

Version 0.97c, released 2026-05-26

## 1 **l3pdfmanagement** documentation

When creating a pdf a number of objects, dictionaries and entries to central “core” dictionaries must be created.

The commands in this module offer interfaces to this core PDF dictionaries. They unify a number of primitives like the pdftex registers and commands `\pdfcatalog`, `\pdfpageattr`, `\pdfpagesattr`, `\pdfinfo`, `\pdfpageresources` and similar commands of the other backends in a backend independent way.

The supported backends are pdf<sub>l</sub>atex, lua<sub>l</sub>atex, (x)dvipdfmx (latex, xelatex and—starting in texlive 2021—lua<sub>l</sub>atex) and dvips with ps2pdf (not completely yet). dvips with distiller could work too but is untested.

That the interfaces are backend independent doesn’t mean that the results and even the compilation behavior is identical. The backends are too different to allow this. Some backends expand arguments e.g. in a `\special` while other don’t. Some backends can insert a resource at the first compilation, while another uses the aux-file and a label and so needs at least two. Some backends create and manage resources automatically which must be managed manually by other backends.

The dictionaries and resources handled by this module are inserted only once in a PDF or only once per page. Examples are the Catalog dictionary, the Info dictionary, the page resources. For these dictionaries and resources management by the L<sup>A</sup>T<sub>E</sub>X kernel is necessary to avoid that packages overwrite settings from other packages which would lead to clashes and incompatibilities. It is therefore necessary that *all* packages which want to add content to these dictionaries and resources use the interface provided by this module.

As these dictionaries and resources are so central for the PDF format values to these dictionaries are always added globally. Through the interface values can be added (and in many cases also removed) by users and packages, but the actually writing of the dictionary entries and resources to the PDF is handled by the kernel code.

The interface uses as main name to address the resources *Paths* which follow the names and structure described in the PDF reference. This should make it easy to identify the names needed to insert a specific PDF resources with the new interfaces. All *Paths* have names starting with an uppercase letter.

---

\*E-mail: [latex-team@latex-project.org](mailto:latex-team@latex-project.org)

The following tabular summarize the *Paths* and which pdftex primitive they replace:

Info	<code>\pdfinfo</code>
Catalog & various subdictionaries	<code>\pdfcatalog</code>
Pages	<code>\pdfpagesattr</code>
Page, ThisPage	<code>\pdfpageattr</code>
Page/Resources/ExtGState	<code>\pdfpageresources</code>
Page/Resources/Shading	<code>\pdfpageresources</code>
Page/Resources/Pattern	<code>\pdfpageresources</code>
Page/Resources/ColorSpace	<code>\pdfpageresources</code>

There is no `Page/Resources/Properties` dictionary in the list, because this dictionary is not filled directly, but managed through side effects when setting BDC-marks.

## 1.1 User Commands

To avoid problems with older documents the resource management of this module is not activated unconditionally. The values are pushed out to the dictionaries only if a boolean has been set to true. The state can be tested with a conditional.

---

```
\pdfmanagement_if_active_p: *
\pdfmanagement_if_active:TF *
```

---

New: 2020-07-04

---

This conditional tests if the resource management code is active.

---

```
\IfPDFManagementActiveTF
```

---

This is a LaTeX2e version of the conditional

New: 2021-07-23

---

---

<code>\pdfmanagement_add:nnn</code>	<code>\pdfmanagement_add:nnn {&lt;resource path&gt;} {&lt;name&gt;} {&lt;value&gt;}</code>
<code>\pdfmanagement_add:(nne nee eee)</code>	
<code>\PDFManagementAdd</code>	

---

New: 2020-04-06

Updated: 2021-07-23

---

This function puts `{<name>}` `{<value>}` in the PDF resource described by the symbolic name `{<resource path>}`. Technically it stores it globally in an internal property lists and writes it later into the right PDF dictionary<sup>1</sup> Which values for `{<resource path>}` exist is described in the following. `{<name>}` should be a PDF Name without the starting slash. Like with all keys used in PDF dictionaries (see the `l3pdfdict` module) the name is escaped with `\str_convert_pdfname:n` when stored. `{<value>}` should be a valid PDF value for this Name in the target dictionary. `\PDFManagementAdd` is a copy of `\pdfmanagement_add:eee` and so expands all its arguments.

The code works with all major engines but not necessarily in the same way. Most importantly

- The expansion behaviour of the backends can differ. Some backends expand a value always fully when writing to the PDF, with other backends command names could end as strings in the PDF. So one should neither rely on `{<name>}` `{<value>}` to be expanded nor not expanded by the backend commands.
- The number of compilations needed can differ between the engines and backends. Some engines have to use labels and the aux-file to setup the dictionaries and so need at least two compilations to put everything in place.
- dvips doesn't support everything. It is for example not possible to add manually or through side effects a name tree like `/AP` or `/JavaScript`, pdfmark doesn't provide a handler here—at least I didn't find anything suitable.

---

<code>\pdfmanagement_show:n</code>	<code>\pdfmanagement_show:n {&lt;resource path&gt;}</code>
------------------------------------	--

---

New: 2020-04-08

This shows the content of the dictionary targeted by `{<resource path>}` in the log and on the terminal if possible.

It is not reliable for page resources as these are filled at shipout.

It also doesn't show necessarily all the content. For example most backends add automatically entries to the Info dictionary.

---

<code>\pdfmanagement_remove:nn</code>	<code>\pdfmanagement_remove:nn {&lt;resource path&gt;} {&lt;name&gt;}</code>
---------------------------------------	--

---

New: 2020-04-07

Removes `/<name>` and its associated `<value>` from the dictionary described with `{<resource path>}` The removal is global. If `<name>` is not found no change occurs, *i.e* there is no need to test for the existence of a name before trying to remove it. Values from the special Catalog entries where the values are collected in arrays can't be removed (but should ever a use case appear it could be added).

## 1.2 Description of the resource paths

---

<sup>1</sup>Currently all resources are PDF dictionaries, so resource and dictionary mean the same.

### 1.2.1 Info: The Info dictionary



If the primitive commands of the engines are used too there will be double entries in the pdf (at least with the backend pdftex and luatex). How pdf viewer handles this is unpredictable.

---

pdfmanagement: Info	<code>\pdfmanagement_add:nnn {Info} {&lt;name&gt;} {&lt;value&gt;}</code>
---------------------	---

---

Adds `/<name>` and the `<value>` to the Info dictionary. `<name>` should be a PDF name without the leading slash, Like with all keys used in PDF dictionaries (see the `l3pdfdict` module) the name is escaped with `\str_convert_pdfname:n` when stored. `<value>` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. If a `<name>` is used twice, only the last `<value>` set will be used. The Info dictionary is written at the end of the compilation, so values can be set at any time. The Info dictionary expects utf16be in the strings, so a conversion like this is normally sensible:

```
\str_set_convert:Nnnn \l_tmpa_str { Grüße }{ default } {utf16/string}  
\pdfmanagement_add:nne {Info} {Title}{(\l_tmpa_str)}
```

The entries in Info dictionary are rather special as the engines/backends adds some core entries, and changing or removing these entries is not always possible.

The special entries are

**Producer** Added by all engines and backends. Removing the entry is only possible with luatex with `\pdfvariable suppressoptionalinfo 128`. Changing is possible with `\pdfmanagement_add:nnn` with the exception of dvips/pstopdf where the entry is always something like `GPL Ghostscript 9.53.3`.

**Creator** Added by all engines and backends. Removal only possible in luatex by adding 16 to the bitset. Changing is possible with the management command.

**CreationDate** Added by all engines and backends. With the exception of dvips/ps2pdf `SOURCE_DATE_EPOCH` is honored. With pdftex it is possible to suppress it with `\pdfinfoomitdate = 1`, and in luatex by adding 32 to the bitset. Changing is possible with the management command and will overwrite an epoch setting.

**ModDate** Added by all engines and backends with the exception of xdvipdfmx. With the exception of dvips/ps2pdf `SOURCE_DATE_EPOCH` is honored. Suppressing it is possible in pdftex with `\pdfinfoomitdate = 1`, and in luatex by adding 64 to the bitset. Changing is possible with the management command.

**Trapped** Added by pdftex and luatex. Removal only possible in luatex by adding 256 to the bitset. Changing (and adding in the other backends) is possible with the management command.

**PTEX.Fullbanner** Added by pdftex and luatex. Removal possible in pdftex with `\pdfsuppressptexinfo-1`, in luatex by adding 512 to the bitset. Changing is not possible.

**Title** Added by dvips/ps2pdf and set to `filename.dvi`. Removal is probably not possible, but it can be overwritten with the management command.

## 1.2.2 Pages: The “Pages” dictionary



As the content of this dictionary is written at the end it will in pdfTeX and LuaTeX overwrite values added with the primitive commands (e.g. `\pdfpagesattr`. Package authors should use the management commands instead.

By using this path with the pdfmanagement interface, values can be added to the /Pages object. This replaces for example `\pdfpagesattr`.

---

**pdfmanagement: Pages** `\pdfmanagement_add:nnn {Pages} {<name>} {<value>}`

---

Adds `/<name> <value>` to the /Pages dictionary. It is always stored globally. The content is written to the pdf at the end of the compilation, so values can be added, changed or removed until then. `<name>` should be a valid pdf name without the leading slash, `<value>` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. Some backends expand the value but this should not be relied on. If a `<name>` is used twice, only the last `<value>` set will be used.

## 1.2.3 “Page” and “ThisPage”

---

**pdfmanagement: Page** `\pdfmanagement_add:nnn {Page} {<name>} {<value>}`

---

New: 2020-04-12

Values added with the path **Page** are added to the page dictionary of the current page and the following pages. The current page means the page on which the command is *executed*. `<name>` should be a valid pdf name without the leading slash. Typical names used here are e.g. **Rotate** and **CropBox**. `<value>` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. Some backends expand the value but this should not be relied on. To avoid problems with the asynchronous page breaking the command should be used after `\newpage` or in the header. It should not be used in a float, as it will then quite probably be executed on the wrong page. The value is assigned directly and is always stored globally. If a `<name>` is used twice, only the last `<value>` set will be used. Names set with `\pdfmanagement_add:nnn{ThisPage}` will overwrite names set with `\pdfmanagement_add:nnn{Page}` if there is a clash. Values can be removed again with `\pdfmanagement_remove:nn`. This replaces `\pdfpageattr`.

---

**pdfmanagement: ThisPage** `\pdfmanagement_add:nnn {ThisPage} {<name>} {<value>}`

---

New: 2020-04-12

Adds `/<name> <value>` at *shipout* to the page dictionary of the current page. Current page means here the *shipout* page. *shipout* means at the end of the `shipout/background` hook. Code that wants to set a value in a shipout hook should use the `shipout/background` hook too. Other hooks are either too early or too late. It is always stored globally. If `{<name>}` has already a value set in the **Page** dictionary it will be overwritten for this page. `<name>` should be a valid pdf name without the leading slash, `<value>` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. If a `<name>` is used twice, only the last `<value>` set will be used. With the engine pdfLaTeX (at least) a second compilation is needed. Values added to **ThisPage** can not be removed. It is not possible to show the content of this dictionary with `\pdfmanagement_show:n`.

**Changing the /MediaBox** : It is possible to change the /MediaBox of one or more pages by setting it for the **Page** or **ThisPage** path (using **Pages** doesn’t work, the engines overwrite this)—this works even with dvips and allows to create pages of different sizes. But you must be careful with the values. If you set e.g. with pdfLaTeX `\pdfpageheight`

to 300bp you get a mediabox of 0 0 595 300, but pdf<sub>l</sub>atex measure from the top and will also move the reference point up, so effectively you get the *upper* third of the page. If you set the /MediaBox to 0 0 595 300 with \pdfmanagement\_add:nnn you get the *lower* third. In general it is better to use only the primitive commands to avoid confusing results.

### 1.2.4 “Page/Resources”: ExtGState, ColorSpace, Shading, Pattern

---

```
pdfmanagement: Page/Resources/ExtGState \pdfmanagement_add:nnn {Page/Resources/<resource>} {<name>} {<value>}
pdfmanagement: Page/Resources/ColorSpace
pdfmanagement: Page/Resources/Shading
pdfmanagement: Page/Resources/Pattern
```

---

Updated: 2020-04-10

Adds /<name> <value> to the page resource <resource>. <resource> can be ExtGState, ColorSpace, Pattern or Shading. The values are always stored globally. The content is written to the pdf at the end of the compilation, so values can be added until then. <name> should be a valid pdf name without the leading slash, <value> should be a valid pdf value for the resource. Any escaping or (re)encoding must be done explicitly. If a <name> is used twice, only the last <value> set will be used.

With the dvips backend the command does nothing: these resources are managed by ghostscript or the distiller if e.g. transparency is used.

The resources are added to all pages starting with the first where something has been added to a resources. That means that for example all ExtGState resources are combined in one dictionary object and every page with a ExtGState resource refer to this object <sup>2</sup>.



The primitive commands (e.g. \pdfpagemresources) to set the resources should not be used together with this code as the calls will overwrite each other and values will be lost. This means that currently there are clashes with the packages tikz, transparent and colorspace.

### 1.2.5 “Catalog” & subdirectories

The catalog is a central dictionary in a PDF with a number of subdictionaries. Entries to the top level of the catalog can be added with

```
\pdfmanagement_add:nnn {Catalog}{<Name>}{<Value>}. Entries to subdictionaries by using in the first argument one of the paths described later. The entries in the catalog have varying requirements regarding the PDF management. Some entries (like /Lang) are simple values where new values should overwrite existing values, other like for example /OutputIntents can contain a number of values and can be filled from more than one source. In some cases the values that needs to be added are not at the top-level but in some subsubdictionary or are actually part of an array. To handle the pdf management uses a variety of internal, special handlers.
```



In some cases entries are added implicitly. For example entries to the name tree of the /EmbeddedFiles key in the /Names directory are added with the commands of the l3pdf<sub>l</sub>file module. This clashes with e.g. the embedfile package which should not be used!

---

<sup>2</sup>This is similar to how pgf handles this resources

**Entries at the top level of the catalog** The Names in the following tabular are entries that are added to the top level of the catalog.

If  $\langle \text{Name} \rangle$  gets assigned a value more than once the last one wins. There is no check that the values have the correct type and format. It is up to the user to ensure that the value does what is intended.

The required PDF version is only mentioned if it is larger than 1.5.

Example: `\pdfmanagement_add:nnn {Catalog}{PageMode}{/UseNone}`

Name	Value	Remark
Collection	objref or dict	the content should be build by external packages (see eg embedfile)
DPartRoot	objref or dict	PDF 2.0
Lang	string	e.g. (de-DE)
Legal	objref or dict	
Metadata	objref or stream	
NeedsRendering	boolean	PDF 1.7
OpenAction	array (dest) or dict (action)	
PageLabels	objref or dict	number tree
PageLayout	name	one of /SinglePage, /OneColumn, /TwoColumnLeft, /TwoColumnRight, /TwoPageLeft, /TwoPageRight
PageMode	name	one of /UseNone, /UseOutlines, /UseThumbs, /UseOC, /UseAttachments (PDF 1.6)
Perms	objref or dict	permissions
PieceInfo	objref or dict	
SpiderInfo	objref or dict	
StructTreeRoot	objref or dict	
Threads	objref to an array	
URI	objref or dict	
Version	name	eg. /1.7
$\langle \text{unknown} \rangle$		an unknown $\langle \text{name} \rangle$ will be inserted without a warning.

**Simple entries in subdictionaries of the catalog** The following resource paths have been predeclared and allow to add values to the respective subdictionaries of the catalog. The names of the dictionaries follow the naming and location of the dictionaries in the PDF reference. If  $\langle \text{Name} \rangle$  gets assigned two values the last one wins.

Example: `\pdfmanagement_add:nnn {Catalog/MarkInfo}{Marked}{true}`

Path/dictionary	Names	Value	Remark
Catalog/AA	WC, WS, DS, WP,DP	all dict	
Catalog/AcroForm	NeedAppearances	boolean	In pdf 2.0 NeedAppearances is deprecated, it is then required that every widget has an appearance streams.
	SigFlags	Integer	
	DA	String	
	Q	Integer	
	XFA	stream or array	
Catalog/AcroForm/DR	<i>&lt;name&gt;</i>		pdf 1.5 probably unneeded
Catalog/AcroForm/DR/Font	<i>&lt;name&gt;</i>	dict	
Catalog/MarkInfo	Marked	boolean	
	UserProperties	boolean	
	Suspects	boolean	
Catalog/ViewerPreferences	HideToolbar	boolean	
	Direction	/R2L or /L2R	
	...		many more, see the reference

**Catalog entries with multiple values in arrays** The following entries are special: Their values are arrays and it must be possible to append to such arrays. This means that a new call to set this value doesn't replace the value but appends it. The value is an object reference. It is sensible to declare the object first. E.g.

```

\pdf_object_new:n      {module/intent}
\pdf_object_write:nnn {module/intent}{dict}{...}
\pdfmanagement_add:nne {Catalog} {OutputIntents}{\pdf_object_ref:n {module/intent}}

```

or

```

\pdf_object_unnamed_write:nn {dict} { ... }
\pdfmanagement_add:nne {Catalog} {OutputIntents}{\pdf_object_ref_last:}

```



Path/dictionary	Name	Value	Remark
Catalog/AcroForm	Fields	object reference	
Catalog/AcroForm	CO	object reference	
Catalog	AF	object reference	PDF 2.0, associated files
Catalog/OCProperties	OCGs	object reference	if there are OCProperties, OCGs and D are required.
Catalog/OCProperties	Configs	object reference	
Catalog/OCProperties	D	object reference	This is actually a single value as there can be only one default. If the value is set twice, the second wins, and the first is added to OCProperties/Configs.
Catalog	OutputIntents	object reference	
Catalog	Requirements	object reference	PDF 1.7
Catalog/Names	EmbeddedFiles	object reference	This should reference a filespec dictionary. It will attach the file to the file panel.

**Catalog entries for name trees** *Not supported in the dvips backend, pdfmark doesn't have an interface here.*

In various places the PDF format allows to reference objects by name instead of by object reference. The relationship between a name and the object reference are store in so-called *name trees*, which are stored in the Catalog/Names dictionary. The `/Dests` and the `/EmbeddedFiles` name trees are handled implicitly if destinations or files are added. Names to the other name trees can be added with `\pdfmanagement_add:nnn`, e.g. to add an value to the AP names (for appearance streams) use

```
\pdfmanagement_add:nne { Catalog / Names / AP } {myAPname} {\pdf_object_ref_last:}
```

Remarks:

- The name `myAPname` is processed through `\pdf_string_from_unicode:nnN{utf8/string}` and parentheses are added automatically. Ensure that the use of the name handles it in the same way.
- It is currently not possible to test if a name has already been used by another package or previous code, so use names where you can be confident that they are unique. (It would be possible to split up the first part and test, but it would slow down the compilation and I'm not sure if it is worth the trouble)
- The value is not preprocessed, it is up-to-you to ensure that it does the right thing.
- Currently the structure of the name tree is flat, it doesn't use Kids. But this can be changed if the need arise.

The following name trees can be filled with this method. Currently only the first three are activated. For the first, `EmbeddedFiles` there are two methods to add a value: `\pdfmanagement_add:nnn{Catalog/Names/EmbeddedFiles}{name}{reference}` and `\pdfmanagement_add:nnn{Catalog/Names/EmbeddedFiles}{name}{reference}`. This is intended, the second methods creates a name on the fly (with the prefix `l3ef`)

Catalog/Names/EmbeddedFiles	A name tree mapping name strings to file specifications for embedded files
Catalog/Names/AP	A name tree mapping name strings to annotation appearance
Catalog/Names/JavaScript	A name tree mapping name strings to documentlevel ECMAScript
(inactive) Catalog/Names/Pages	A name tree mapping name strings to visible pages for use in the document
(inactive) Catalog/Names/Templates	A name tree mapping name strings to invisible pages for use in the document
(inactive) Catalog/Names/IDS	A name tree mapping digital identifiers to Web.Capture content
(inactive) Catalog/Names/URLS	A name tree mapping name strings to documentlevel ECMAScript
(inactive) Catalog/Names/Renditions	A name tree mapping name strings (which shall have Unicode characters)

## 2 l3pdfmanagement implementation

```

1 <@@=pdfmanagement>
2 <*header>
3 %
4 \ProvidesExplPackage{l3pdfmanagement}{2026-05-26}{0.97c}
5 {Management of core PDF dictionaries (LaTeX PDF management bundle)}
6 </header>

```

### 2.1 Messages

```

7 <*package>
8 \msg_new:nnn { pdfmanagement } { unknown-dict }
9 { The~PDF~management~resource~'#1'~is~unknown. }
10
11 \msg_new:nnn { pdfmanagement } { empty-value }
12 { The~value~for~#1~is~empty~and~will~be~ignored }
13
14 \msg_new:nnn { pdfmanagement } { no-removal }
15 { It~is~not~possible~to~remove~values~from~'#1'~.}
16
17 \msg_new:nnn { pdfmanagement } { no-show }
18 { It~is~not~possible~to~show~the~content~of~'#1'~.}
19
20 \msg_new:nnn { pdfmanagement } { name-exist }
21 { The~name~'#1'~has~already~been~used~for~name~tree~'#2'~.}
22
23 \msg_new:nnn { pdfmanagement } { show-dict }
24 {
25   The~PDF~resource~'#1'~
26   \tl_if_empty:nTF {#2}
27   { is~empty \>~ . }
28   { contains~the~pairs~(without~outer~braces): #2 . }
29 }
30 \msg_new:nnn { pdfmanagement } { dict-already-defined }
31 {
32   The~path~'#1'~is~already~defined.
33 }

```

```

34 \msg_new:nnn { pdfmanagement } { inactive }
35 {
36   The~PDF~resources~management~is~not~active\\
37   command~'#1'~ignored.
38 }

```

Some temp variables

```

\l__pdfmanagement_tmpa_tl
\l__pdfmanagement_tmpb_tl
\l__pdfmanagement_tmpa_seq

```

```

39 \tl_new:N \l__pdfmanagement_tmpa_tl
40 \tl_new:N \l__pdfmanagement_tmpb_tl
41 \seq_new:N \l__pdfmanagement_tmpa_seq

```

(End of definition for \l\_\_pdfmanagement\_tmpa\_tl, \l\_\_pdfmanagement\_tmpb\_tl, and \l\_\_pdfmanagement\_tmpa\_seq.)

```
\g_pdfmanagement_active_bool
```

This boolean will controlled the activation of the management code. It is now a noop and always true.

```

42 \bool_new:N \g_pdfmanagement_active_bool
43 \bool_gset_true:N \g_pdfmanagement_active_bool

```

(End of definition for \g\_pdfmanagement\_active\_bool.)

A user predicate to test if the management code is active

```

44 \prg_new_conditional:Npnn \__pdfmanagement_if_active: { p , T , F , TF }
45 {
46   \prg_return_true:
47 }
48 \prg_set_eq_conditional:NNn
49 \pdfmanagement_if_active: \__pdfmanagement_if_active: { p , T , F , TF }
50
51 \cs_set_eq:NN \IfPDFManagementActiveTF\use_i:nn

```

We use a hook, to collect value added before the backend is ready.

```

52 \hook_new:n {pdfmanagement/add}
53 \cs_new_protected:Npn \pdfmanagement_add:nnn #1 #2 #3
54 {
55   \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
56   {
57     \hook_gput_code:nnn
58     {pdfmanagement/add}
59     {pdfmanagement}
60     {
61       \__pdfmanagement_handler_gput:nnn { #1 } { #2 } { #3 }
62     }
63   }
64   {
65     \msg_error:nnn{pdfmanagement}{unknown-dict}{#1}
66   }
67 }
68
69 \cs_generate_variant:Nn \pdfmanagement_add:nnn {nne,nee,eee,nnx,nxx,xxx}
70 \cs_set_eq:NN \PDFManagementAdd \pdfmanagement_add:eee

```

## 2.2 Hooks – shipout and end of run code

Code is executed in three places: At shipout of every page, at shipout of the last page, at the end of the document (after the last clearpage). Due to backend differences the code in the three places (and the exact timing) can be different: pdf<sub>l</sub>atex/lualatex can execute code after the last `\clearpage` which the dvi-based drivers have to add on a shipout page.

`\g__kernel_pdfmanagement_end_run_code_tl`

This variables contain the code run in the three places.

```

71 \tl_new:N \g__kernel_pdfmanagement_thispage_shipout_code_tl
72 \tl_new:N \g__kernel_pdfmanagement_lastpage_shipout_code_tl
73 \tl_new:N \g__kernel_pdfmanagement_end_run_code_tl

(End of definition for \g__kernel_pdfmanagement_thispage_shipout_code_tl      \g__kernel_pdfmanagement_
lastpage_shipout_code_tl      \g__kernel_pdfmanagement_end_run_code_tl.)

74 \tl_gset:Nn \g__kernel_pdfmanagement_thispage_shipout_code_tl
75 {
76   \exp_args:NV \__pdf_backend_ThisPage_gpush:n { \g_shipout_readonly_int }
77   \exp_args:NV \__pdf_backend_PageResources_gpush:n { \g_shipout_readonly_int }
78 }
79
80 \tl_gset:Nn \g__kernel_pdfmanagement_end_run_code_tl
81 {
82   \__pdf_backend_PageResources_obj_gpush:          %ExtGState etc
83   \__pdfmanagement_Pages_gpush:                   %pagesattr
84   \__pdfmanagement_Info_gpush:                     %pdfinfo
85   \__pdfmanagement_Catalog_gpush:
86 }
```

## 2.3 Naming convention

Currently the following names are used: All have internally additionally a **Core** before the slash, to hide the real name a bit.

```

/Info                                %    (\pdfinfo)
/Catalog                             %    (\pdfcatalog)
/Catalog/AA                          %
/Catalog/AcroForm
/Catalog/OCProperties
/Catalog/OutputIntents
/Catalog/AcroForm/DR
/Catalog/AcroForm/DR/Font
/Catalog/MarkInfo
/Catalog/ViewerPreferences
/Pages                               %    (\pagesattr)
/Page                                %    (\pageattr)
/ThisPage                            %    (\pageattr)
/backend_PageN/Resources/Properties % this is only internal.
/Page/Resources/ExtGState
/Page/Resources/ColorSpace
/Page/Resources/Pattern
/Page/Resources/Shading
```

```

/Page/Resources/Properties
/Xform/Resources/Properties

```

```

__pdfmanagement_handler_gput:nnn
__pdfmanagement_get:nnN
__pdfmanagement_gremove:nn
__pdfmanagement_show:n

```

`__pdfmanagement_handler_gput:nnn` is the main command to fill the dictionaries. In simple cases it directly fill the property list, but if a handler exists this is called. It is important to use it only in places where this make sense.

```

87 %global
88 \cs_new_protected:Npn __pdfmanagement_handler_gput:nnn #1 #2 #3 % #1 dict, #2 name, #3 value
89 {
90   \tl_if_empty:nTF { #3 }
91   {
92     \msg_none:nnn { pdfmanagement } { empty-value } { /#1/#2 }
93   }
94   {
95     \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
96     {
97       \cs_if_exist:cTF
98       { __pdfmanagement_handler/#1/?_gput:nn } %general, name independent handler
99       { \use:c {__pdfmanagement_handler/#1/?_gput:nn} {#2} {#3} }
100       {
101         \cs_if_exist:cTF
102         { __pdfmanagement_handler/#1/#2_gput:n }
103         { \use:c {__pdfmanagement_handler/#1/#2_gput:n} {#3} } %special handler
104         {
105           \exp_args:Nne
106           \prop_gput:cnn
107           { __kernel_pdfdict_name:n { g__pdf_Core/#1 } }
108           { \str_convert_pdfname:n { #2 } }
109           { #3 }
110         }
111       }
112     }
113     {
114       \msg_error:nnn { pdfmanagement } { unknown-dict } { #1 }
115     }
116   }
117 }
118
119
120 \cs_generate_variant:Nn __pdfmanagement_handler_gput:nnn {nee}
121
122 \cs_new_protected:Npn __pdfmanagement_get:nnN #1 #2 #3 %path,key,macro
123 {
124   \exp_args:Nne
125   \prop_get:cnN
126   { __kernel_pdfdict_name:n { g__pdf_Core/#1 } }
127   { \str_convert_pdfname:n {#2} } #3
128 }
129
130
131 \cs_new_protected:Npn __pdfmanagement_handler_gremove:nn #1 #2 %path,key
132 {
133   \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
134   {

```

```

135         \cs_if_exist:cTF
136         { __pdfmanagement_handler/#1/?_gremove:n } %general, name independent handler
137         { \use:c {__pdfmanagement_handler/#1/?_gremove:n} {#2} }
138         {
139             \cs_if_exist:cTF
140             { __pdfmanagement_handler/#1/#2_gremove: }
141             { \use:c {__pdfmanagement_handler/#1/#2_gremove:} } %special handler
142             {
143                 \exp_args:Nne
144                 \prop_gremove:cn
145                 { \__kernel_pdfdict_name:n { g__pdf_Core/#1 } }
146                 { \str_convert_pdfname:n {#2} }
147             }
148         }
149     }
150     {
151         \msg_error:nnn { pdfmanagement } { unknown-dict } { #1 }
152     }
153 }
154
155 \cs_new_protected:Npn \__pdfmanagement_gremove:nn #1 #2 %path,key
156 {
157     \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
158     {
159         \exp_args:Nne
160         \prop_gremove:cn
161         { \__kernel_pdfdict_name:n { g__pdf_Core/#1 } }
162         { \str_convert_pdfname:n{#2} }
163     }
164     {
165         \msg_error:nnn { pdfmanagement } { unknown-dict } { #1 }
166     }
167 }
168
169
170 \cs_new_protected:Npn \__pdfmanagement_show:Nn #1#2
171 {
172     \cs_if_exist:cTF
173     { __pdfmanagement_handler/#2/?_show: } %general, name independent handler
174     { \use:c {__pdfmanagement_handler/#2/?_show:} }
175     {
176         \prop_if_exist:cTF { \__kernel_pdfdict_name:n { g__pdf_Core/#2 } }
177         {
178             #1
179             { pdfmanagement } { show-dict }
180             { \tl_to_str:n {#2} }
181             {
182                 \prop_map_function:cN
183                 { \__kernel_pdfdict_name:n { g__pdf_Core/#2 } }
184                 \msg_show_item:nn
185             }
186             { } { }
187         }
188     }

```

```

189         #1 { pdfmanagement } { unknown-dict } {#2}{ }{ }
190     }
191 }
192 }
193
194 \cs_new_protected:Npn \__pdfmanagement_show:n #1 %path
195 {
196     \prop_show:c { \__kernel_pdffdict_name:n { g__pdf_Core/#1 } }
197 }

```

(End of definition for \\_\_pdfmanagement\_handler\_gput:nnn and others.)

```

198 \cs_new_protected:Npn \pdfmanagement_show:n #1
199 {
200     \__pdfmanagement_show:Nn \msg_show:nneeee {#1}
201 }
202
203 \cs_new_protected:Npn \pdfmanagement_remove:nn #1 #2
204 {
205     \pdffdict_if_exist:nTF { g__pdf_Core/#1 }
206     {
207         \__pdfmanagement_handler_gremove:nn { #1 }{ #2 }
208     }
209     {
210         \msg_error:nnn{pdfmanagement}{unknown-dict}{#1}
211     }
212 }
213
214 \cs_new_protected:Npn \pdfmanagement_get:nnN #1 #2 #3
215 {
216     \pdffdict_if_exist:nTF { g__pdf_Core/#1 }
217     {
218         \__pdfmanagement_get:nnN { #1 }{ #2 } #3
219     }
220     {
221         \msg_error:nnn{pdfmanagement}{unknown-dict}{#1}
222     }
223 }

```

## 2.4 The Info dictionary

Initialization of the dictionary:

```

222 \pdffdict_new:n { g__pdf_Core/Info}

```

\\_\_pdfmanagement\_Info\_gpush: \\_\_pdfmanagement\_Info\_gpush: is the command that outputs the info dictionary (currently in the end-of-run hooks).

```

223 % push to the register command / issue the special
224 \cs_new_protected:Npn \__pdfmanagement_Info_gpush:
225 {
226     \prop_map_function:cN
227     { \__kernel_pdffdict_name:n { g__pdf_Core/Info} }
228     \__pdf_backend_info_gput:nn
229     \prop_gclear:c { \__kernel_pdffdict_name:n { g__pdf_Core/Info} }
230 }

```

(End of definition for \\_\_pdfmanagement\_Info\_gpush:.)

## 2.5 The Pages dictionary code

At first the initialisation

```
231 \pdfdict_new:n { g__pdf_Core/Pages}
```

`\__pdfmanagement_Pages_gpush:` This is the command that outputs the Pages dictionary. It is used at the end of the document in `\g__pdf_backend_end_run_tl`

```
232 % push to the register command / issue the special
233 \cs_new_protected:Npn \__pdfmanagement_Pages_gpush:
234 {
235   \pdfdict_if_empty:nF { g__pdf_Core/Pages}
236   {
237     \exp_args:Ne \__pdf_backend_Pages_primitive:n
238     {
239       \pdfdict_use:n { g__pdf_Core/Pages}
240     }
241   }
242 }
243
```

*(End of definition for \\_\_pdfmanagement\_Pages\_gpush:.)*

## 2.6 The Page and ThisPage dictionary

At first the initialisation.

```
244 \pdfdict_new:n { g__pdf_Core/Page }
245 \pdfdict_new:n { g__pdf_Core/ThisPage }
246
247 %handler for pdfmanagement
248 \cs_new_protected:cpn { __pdfmanagement_handler/Page/?_gput:nn } #1 #2
249 {
250   \__pdf_backend_Page_gput:nn { #1 }{ #2 }
251 }
252 % remove:
253 \cs_new_protected:cpn { __pdfmanagement_handler/Page/?_gremove:n } #1
254 {
255   \__pdf_backend_Page_gremove:n { #1 }
256 }
257
258 % handler for pdfmanagement
259 \cs_new_protected:cpn { __pdfmanagement_handler/ThisPage/?_gput:nn } #1 #2
260 {
261   \prop_gput:cnn { \__kernel_pdfdict_name:n { g__pdf_Core/ThisPage } }{ #1 } { #2 }
262   \__pdf_backend_ThisPage_gput:nn { #1 }{ #2 }
263 }
264
265 \cs_new_protected:cpn { __pdfmanagement_handler/ThisPage/?_gremove:n } #1
266 {
267   \msg_warning:nnn { pdfmanagement } { no-removal }{ThisPage}
268 }
269
270 \cs_new_protected:cpn { __pdfmanagement_handler/ThisPage/?_show: }
271 {
272   \msg_warning:nnn { pdfmanagement } { no-show }{ThisPage}
```



```

273     }
274

```

### 2.6.1 “Page/Resources”: ExtGState, ColorSpace, Shading, Pattern

```

275 \clist_const:Nn \c__pdfmanagement_PageResources_clist
276 {
277     ExtGState,
278     ColorSpace,
279     Pattern,
280     Shading,
281 }
282
283 \clist_map_inline:Nn \c__pdfmanagement_PageResources_clist
284 {
285     \pdfdict_new:n { g__pdf_Core/Page/Resources/#1}
286 }
287 %
288 % setter: #1 is the name of the resource
289 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/ExtGState/?_gput:nn } #1 #2
290 {
291     __pdf_backend_PageResources_gput:nnn {ExtGState} { #1 }{ #2 }
292 }
293
294 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/ColorSpace/?_gput:nn } #1 #2
295 {
296     __pdf_backend_PageResources_gput:nnn {ColorSpace} { #1 }{ #2 }
297 }
298
299 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/Shading/?_gput:nn } #1 #2
300 {
301     __pdf_backend_PageResources_gput:nnn {Shading} { #1 }{ #2 }
302 }
303
304 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/Pattern/?_gput:nn } #1 #2
305 {
306     __pdf_backend_PageResources_gput:nnn {Pattern} { #1 }{ #2 }
307 }

```

### 2.6.2 “Catalog”

The catalog has mixed entries: toplevel, subdictionaries, and entries which must build arrays.

```

\c__pdfmanagement_Catalog_toplevel_clist
\c__pdfmanagement_Catalog_sub_clist
\c__pdfmanagement_Catalog_seq_clist

```

This variables hold the list of the various types of entries. With it the various `_gput` commands are generated.  
(End of definition for `\c__pdfmanagement_Catalog_toplevel_clist`, `\c__pdfmanagement_Catalog_sub_clist`, and `\c__pdfmanagement_Catalog_seq_clist`.)

```

\__pdfmanagement_catalog_XX_gput:n

```

Various commands to handle subentries and special cases. At first we set up a few lists of the various types.

```

308 \pdfdict_new:n { g__pdf_Core/Catalog}
309
310 \clist_const:Nn \c__pdfmanagement_Catalog_toplevel_clist

```

```

311 {
312     Collection,
313     DPartRoot,
314     Lang,
315     Legal,
316     Metadata,
317     NeedsRendering,
318     OCProperties/D,
319     OpenAction,
320     PageLabels,
321     PageLayout,
322     PageMode,
323     Perms,
324     PieceInfo,
325     SpiderInfo,
326     StructTreeRoot,
327     Threads,
328     URI,
329     Version
330 }
331
332 \clist_const:Nn \c__pdfmanagement_Catalog_sub_clist
333 {
334     AA,
335     AcroForm,
336     AcroForm/DR,
337     AcroForm/DR/Font,
338     MarkInfo,
339     ViewerPreferences,
340     OCProperties
341 }
342
343 \clist_map_inline:Nn \c__pdfmanagement_Catalog_sub_clist
344 {
345     \pdfdict_new:n { g__pdf_Core/Catalog/#1}
346 }
347
348
349 \clist_const:Nn \c__pdfmanagement_Catalog_seq_clist
350 {
351     AF,
352     OCProperties/OCGs,
353     OCProperties/Configs,
354     OutputIntents,
355     Requirements,
356     AcroForm/Fields,
357     AcroForm/CO
358 }
359

```

Names trees in Catalog/Names. We prepare the full list but activate only AP and JavaScript for now. /EmbeddedFiles has special code and so is not in the name list.

```

360 \clist_const:Nn \c__pdfmanagement_Catalog_nametree_clist
361 {

```

```

362     AP,
363     JavaScript,
364     % Pages,
365     % Templates,
366     % IDS,
367     % URLs,
368     % Renditions
369 }

```

now we create the handler. The entries in the seq-list store in a seq

```

370 \clist_map_inline:Nn \c__pdfmanagement_Catalog_seq_clist
371 {
372     \seq_new:c { g__pdfmanagement_/Catalog/#1_seq } % new name later
373     \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/#1_gput:n } ##1
374     {
375         \seq_gput_right:cn { g__pdfmanagement_/Catalog/#1_seq } { ##1 }
376     }
377 }
378

```

OCProperties/D is special: it handles a default. This is done by adding to the left of the seq

```

379 \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/OCProperties/D_gput:n } #1
380 {
381     \seq_gput_left:cn
382     { g__pdfmanagement_/Catalog/OCProperties/Configs_seq }
383     { #1 }
384 }

```

The name tree keys store in a property and check for duplicates. This is done with an auxiliary.

```

385 \cs_new_protected:Npn \__pdfmanagement_nametree_add_aux:nnn #1 #2 #3
386     % #1 name tree, #2 sanitized name #3 value
387     {
388         \prop_get:coNTF
389         { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/Names/#1 }}
390         { #2 }
391         \l__pdfmanagement_tmpb_tl
392         {
393             \msg_error:nnnn{pdfmanagement}{name-exist}{#2}{#1}
394         }
395         {
396             \prop_gput:con
397             { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/Names/#1 }}
398             { #2 }
399             { #3 }
400         }
401     }

```

This is the standard handler for most names trees:

```

402 \clist_map_inline:Nn \c__pdfmanagement_Catalog_nametree_clist
403 {
404     \pdfdict_new:n { g__pdf_Core/Catalog/Names/#1}
405     \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/Names/#1/?_gput:nn } ##1 ##2

```

```

406     {
407         \pdf_string_from_unicode:nnN {utf8/string}{#1}\l__pdfmanagement_tmpa_tl
408         \exp_args:Nno
409         \__pdfmanagement_nametree_add_aux:nnn {#1}{\l__pdfmanagement_tmpa_tl}{##2}
410     }
411 }

```

EmbeddedFiles is a bit special. For once there is special backend code needed by dvips. Beside this we also want the option to create the file name on the fly, so they are actually two access methods: `\pdfmanagement_add:nnn{Catalog/Names/EmbeddedFiles}{name}{reference}` and `\pdfmanagement_add:nnn{Catalog/Names}{EmbeddedFiles}{reference}`

```

412 \pdfdict_new:n { g__pdf_Core/Catalog/Names/EmbeddedFiles}
413 \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/Names/EmbeddedFiles/?_gput:nn } #1 #2
414 {
415     \pdf_string_from_unicode:nnN {utf8/string}{#1}\l__pdfmanagement_tmpa_tl
416     \exp_args:Nno
417     \__pdfmanagement_nametree_add_aux:nnn
418     {EmbeddedFiles}{\l__pdfmanagement_tmpa_tl}{#2}
419     \exp_args:No
420     \__pdf_backend_NamesEmbeddedFiles_add:nn {\l__pdfmanagement_tmpa_tl}{#2}
421 }

```

*(End of definition for \\_\_pdfmanagement\_catalog\_XX\_gput:n.)*

## Building the catalog: Push order

`\__pdfmanagement_Catalog_gpush:`

```

422 \cs_new_protected:Npn \__pdfmanagement_Catalog_gpush:
423 {
424     \use:c { __pdfmanagement_/Catalog/AA_gpush: }
425     \use:c { __pdfmanagement_/Catalog/AcroForm_gpush: }
426     \use:c { __pdfmanagement_/Catalog/AF_gpush: }
427     \use:c { __pdfmanagement_/Catalog/MarkInfo_gpush: }
428     \pdfmeta_standard_verify:nT {Catalog_no_OCProperties}
429     {
430         \use:c { __pdfmanagement_/Catalog/OCProperties_gpush: }
431     }
432     \use:c { __pdfmanagement_/Catalog/OutputIntents_gpush: }
433     \use:c { __pdfmanagement_/Catalog/Requirements_gpush: }
434     \use:c { __pdfmanagement_/Catalog/ViewerPreferences_gpush: }
435     % output the single values:
436     \prop_map_function:cN
437     { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog} }
438     \__pdf_backend_catalog_gput:nn
439     % output names tree:
440     \use:c{ __pdfmanagement_/Catalog/Names_gpush:n } {EmbeddedFiles}
441     \clist_map_inline:Nn \c__pdfmanagement_Catalog_nametree_clist
442     {
443         \use:c{ __pdfmanagement_/Catalog/Names_gpush:n } {##1}
444     }
445 }

```

*(End of definition for \\_\_pdfmanagement\_Catalog\_gpush:.)*

## Building catalog entries: AA

\\_pdfmanagement\_/Catalog/AA\_gpush:

```
446 \cs_new_protected:cpn { __pdfmanagement_/Catalog/AA_gpush: }
447 {
448   \prop_if_empty:cF
449   { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AA } }
450   {
451     \pdf_object_new:n { __pdfmanagement_/Catalog/AA }
452     \pdf_object_write:nne
453     { __pdfmanagement_/Catalog/AA } { dict }
454     { \pdffdict_use:n { g__pdf_Core/Catalog/AA } }
455     \exp_args:Nne
456     \__pdf_backend_catalog_gput:nn
457     {AA}
458     {
459       \pdf_object_ref:n { __pdfmanagement_/Catalog/AA }
460     }
461   }
462 }
```

(End of definition for \\_\_pdfmanagement\_/Catalog/AA\_gpush:.)

**Building catalog entries: AcroForm** This is the most complicated case. The entries is build from /Catalog/AcroForm/Fields (array), /Catalog/AcroForm/CO (array), /Catalog/AcroForm/DR/Font (dict), /Catalog/AcroForm/DR (dict), /Catalog/AcroForm

\\_pdfmanagement\_/Catalog/AcroForm\_gpush:

```
463 \cs_new_protected:cpn { __pdfmanagement_/Catalog/AcroForm_gpush: }
464 {
465   \seq_if_empty:cF { g__pdfmanagement_/Catalog/AcroForm/Fields_seq }
466   {
467     \pdf_object_new:n { __pdfmanagement_/Catalog/AcroForm/Fields }
468     \pdf_object_write:nne
469     { __pdfmanagement_/Catalog/AcroForm/Fields } { array }
470     { \seq_use:cn { g__pdfmanagement_/Catalog/AcroForm/Fields_seq } {~} }
471     \exp_args:Nnne
472     \prop_gput:cn %we have to use \prop here to avoid the handler ...
473     { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm } }
474     { Fields }
475     { \pdf_object_ref:n { __pdfmanagement_/Catalog/AcroForm/Fields } }
476   }
477   \seq_if_empty:cF { g__pdfmanagement_/Catalog/AcroForm/CO_seq }
478   {
479     \pdf_object_new:n { __pdfmanagement_/Catalog/AcroForm/CO }
480     \pdf_object_write:nne
481     { __pdfmanagement_/Catalog/AcroForm/CO } { array }
482     { \seq_use:cn { g__pdfmanagement_/Catalog/AcroForm/CO_seq } {~} }
483     \exp_args:Nnne
484     \prop_gput:cn %we have to use \prop here to avoid the handler ...
485     { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm } }
486     { CO }
487     { \pdf_object_ref:n { __pdfmanagement_/Catalog/AcroForm/CO } }
488   }
}
```

```

489 \prop_if_empty:cF { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm/DR/Font}}
490 {
491   \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm/DR/Font }
492   \pdf_object_write:nne
493     { __pdfmanagement/Catalog/AcroForm/DR/Font } { dict }
494     { \pdffdict_use:n { g__pdf_Core/Catalog/AcroForm/DR/Font } }
495   \exp_args:Nnne
496     \prop_gput:cnn %we have to use \prop here to avoid the handler ...
497     { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm/DR } }
498     { Font }
499     { \pdf_object_ref:n { __pdfmanagement/Catalog/AcroForm/DR/Font } }
500 }
501 \prop_if_empty:cF { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm/DR}}
502 {
503   \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm/DR }
504   \pdf_object_write:nne
505     { __pdfmanagement/Catalog/AcroForm/DR } { dict }
506     { \pdffdict_use:n { g__pdf_Core/Catalog/AcroForm/DR } }
507   \exp_args:Nnne
508     \prop_gput:cnn %we have to use \prop here to avoid the handler ...
509     { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm } }
510     { DR }
511     { \pdf_object_ref:n { __pdfmanagement/Catalog/AcroForm/DR } }
512 }
513 \prop_if_empty:cF { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm} }
514 {
515   \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm }
516   \pdf_object_write:nne
517     { __pdfmanagement/Catalog/AcroForm } { dict }
518     { \pdffdict_use:n { g__pdf_Core/Catalog/AcroForm } }
519   \exp_args:Nnne
520     \__pdfmanagement_handler_gput:nnn
521     { Catalog }
522     { AcroForm }
523     { \pdf_object_ref:n { __pdfmanagement/Catalog/AcroForm } }
524 }
525 }
526

```

(End of definition for \\_\_pdfmanagement\_/Catalog/AcroForm\_gpush:.)

**Building catalog entries: AF** AF is an array.

\\_\_pdfmanagement\_/Catalog/AF\_gpush:

```

527 \cs_new_protected:cpn { __pdfmanagement_/Catalog/AF_gpush: }
528 {
529   \seq_if_empty:cF
530     { g__pdfmanagement_/Catalog/AF_seq }
531     {
532       \pdf_object_new:n { __pdfmanagement/Catalog/AF }
533       \pdf_object_write:nne
534         { __pdfmanagement/Catalog/AF } { array }
535         { \seq_use:cn { g__pdfmanagement_/Catalog/AF_seq } {~} }
536       \exp_args:Nne

```

```

537         \__pdf_backend_catalog_gput:nn
538         {AF}
539         {
540             \pdf_object_ref:n {__pdfmanagement/Catalog/AF}
541         }
542     }
543 }

```

(End of definition for \\_\_pdfmanagement\_/Catalog/AF\_gpush:.)

## Building catalog entries: MarkInfo

\\_\_pdfmanagement\_/Catalog/MarkInfo\_gpush:

```

544 \cs_new_protected:cpn { __pdfmanagement_/Catalog/MarkInfo_gpush: }
545 {
546     \prop_if_empty:cF
547     { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/MarkInfo } }
548     {
549         \pdf_object_new:n { __pdfmanagement/Catalog/MarkInfo }
550         \pdf_object_write:nne
551         { __pdfmanagement/Catalog/MarkInfo } { dict }
552         { \pdfdict_use:n { g__pdf_Core/Catalog/MarkInfo } }
553         \exp_args:Nne
554         \__pdf_backend_catalog_gput:nn
555         {MarkInfo}
556         {
557             \pdf_object_ref:n {__pdfmanagement/Catalog/MarkInfo}
558         }
559     }
560 }

```

(End of definition for \\_\_pdfmanagement\_/Catalog/MarkInfo\_gpush:.)

## Building catalog entries: OCProperties This is a dictionary with three entries:

**/OCGs** (required) An array of indirect references, access needed for more than one package.

**/D** (required) a dict (given as an object name) to the default configuration

**/Configs** (optional) an array of indirect references to more configurations.

The /D entry is also a config, it is the first of the seq. The overall structure is nested: a dict with arrays.

\\_\_pdfmanagement\_/Catalog/OCProperties\_gpush:

```

561 % Catalog/OCProperties: OCGs + D is required
562 \cs_new_protected:cpn { __pdfmanagement_/Catalog/OCProperties_gpush: }
563 {
564     \int_compare:nNnT
565     {
566         ( \seq_count:c { g__pdfmanagement_/Catalog/OCProperties/OCGs_seq } ) *
567         ( \seq_count:c { g__pdfmanagement_/Catalog/OCProperties/Configs_seq } )
568     }
569     >

```

```

570     { 0 }
571     {
572         \pdf_object_new:n { __pdfmanagement/Catalog/OCProperties }
573         \seq_gpop_left:cN { g__pdfmanagement_/Catalog/OCProperties/Configs_seq } \l__pdfmanag
574         \pdf_object_write:nne {__pdfmanagement/Catalog/OCProperties} {dict}
575         {
576             /OCGs~ [ \seq_use:cn { g__pdfmanagement_/Catalog/OCProperties/OCGs_seq } {~} ]
577             /D~\l__pdfmanagement_tmpa_tl~
578             \seq_if_empty:cF { g__pdfmanagement_/Catalog/OCProperties/Configs_seq }
579             {
580                 /Configs~
581                 [ \seq_use:cn { g__pdfmanagement_/Catalog/OCProperties/Configs_seq } {~} ]
582             }
583         }
584         \exp_args:Nne
585         \__pdf_backend_catalog_gput:nn
586         { OCProperties }
587         { \pdf_object_ref:n {__pdfmanagement/Catalog/OCProperties} }
588     }
589 }

```

(End of definition for \\_\_pdfmanagement\_/Catalog/OCProperties\_gpush:.)

**Building catalog entries: OutputIntents** OutputIntents is an array.

\_pdfmanagement\_/Catalog/OutputIntents\_gpush:

```

590 \cs_new_protected:cpn { __pdfmanagement_/Catalog/OutputIntents_gpush: }
591 {
592     \seq_if_empty:cF
593     { g__pdfmanagement_/Catalog/OutputIntents_seq }
594     {
595         \pdf_object_new:n { __pdfmanagement/Catalog/OutputIntents }
596         \pdf_object_write:nne
597         { __pdfmanagement/Catalog/OutputIntents } { array }
598         { \seq_use:cn { g__pdfmanagement_/Catalog/OutputIntents_seq } {~} }
599         \exp_args:Nne
600         \__pdf_backend_catalog_gput:nn
601         {OutputIntents}
602         {
603             \pdf_object_ref:n {__pdfmanagement/Catalog/OutputIntents}
604         }
605     }
606 }

```

(End of definition for \\_\_pdfmanagement\_/Catalog/OutputIntents\_gpush:.)

**Building catalog entries: Requirements** Requirements is an array.

\_pdfmanagement\_/Catalog/Requirements\_gpush:

```

607 \cs_new_protected:cpn { __pdfmanagement_/Catalog/Requirements_gpush: }
608 {
609     \seq_if_empty:cF
610     { g__pdfmanagement_/Catalog/Requirements_seq }
611     {

```



```

612     \pdf_object_new:n { __pdfmanagement/Catalog/Requirements }
613     \pdf_object_write:nne
614         { __pdfmanagement/Catalog/Requirements } { array }
615         { \seq_use:cn { g__pdfmanagement_/Catalog/Requirements_seq } {~} }
616     \exp_args:Nne
617         \__pdf_backend_catalog_gput:nn
618         {Requirements}
619         {
620             \pdf_object_ref:n { __pdfmanagement/Catalog/Requirements }
621         }
622     }
623 }

```

(End of definition for \\_\_pdfmanagement\_/Catalog/Requirements\_gpush:.)

## Building catalog entries: ViewerPreferences

anagement\_/Catalog/ViewerPreferences\_gpush:

```

624 \cs_new_protected:cpn { __pdfmanagement_/Catalog/ViewerPreferences_gpush: }
625 {
626     \prop_if_empty:cF
627     { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/ViewerPreferences } }
628     {
629         \pdf_object_new:n { __pdfmanagement/Catalog/ViewerPreferences }
630         \pdf_object_write:nne
631             { __pdfmanagement/Catalog/ViewerPreferences } { dict }
632             { \pdfdict_use:n { g__pdf_Core/Catalog/ViewerPreferences } }
633         \exp_args:Nne
634             \__pdf_backend_catalog_gput:nn
635             {ViewerPreferences}
636             {
637                 \pdf_object_ref:n {__pdfmanagement/Catalog/ViewerPreferences}
638             }
639     }
640 }

```

(End of definition for \\_\_pdfmanagement\_/Catalog/ViewerPreferences\_gpush:.)

## Building catalog entries: Names/EmbeddedFiles

\g\_\_pdfmanagement\_EmbeddedFiles\_int

We want to create names for files on the fly. For this we use an int.

```

641 \int_new:N \g__pdfmanagement_EmbeddedFiles_int

```

(End of definition for \g\_\_pdfmanagement\_EmbeddedFiles\_int.)

\\_\_pdfmanagement\_EmbeddedFiles\_name:

We use the prefix l3ef, and pad numbers below 9999.

```

642 \cs_new:Npn \__pdfmanagement_EmbeddedFiles_name:
643 {
644     (
645         l3ef
646         \int_compare:nNtT {\g__pdfmanagement_EmbeddedFiles_int} < {10}
647         {0}
648         \int_compare:nNtT {\g__pdfmanagement_EmbeddedFiles_int} < {100}
649         {0}
650         \int_compare:nNtT {\g__pdfmanagement_EmbeddedFiles_int} < {1000}

```

```

651     {0}
652     \int_use:N \g__pdfmanagement_EmbeddedFiles_int
653   )
654 }

```

(End of definition for \\_\_pdfmanagement\_EmbeddedFiles\_name:.)

\_handler/Catalog/Names/EmbeddedFiles\_gput:n

EmbeddedFiles is an array and needs a special handler to add values.

```

655 \pdfdict_new:n { g__pdf_Core/Catalog/Names }
656
657 \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/Names/EmbeddedFiles_gput:n } #1
658 {
659   \int_gincr:N \g__pdfmanagement_EmbeddedFiles_int
660   \exp_args:Nne
661   \prop_gput:cnn
662     { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/Names/EmbeddedFiles }}
663     { \__pdfmanagement_EmbeddedFiles_name: }
664     { #1 }
665   \exp_args:Ne
666   \__pdf_backend_NamesEmbeddedFiles_add:nn {\__pdfmanagement_EmbeddedFiles_name:} { #1 }
667 }

```

(End of definition for \\_\_pdfmanagement\_handler/Catalog/Names/EmbeddedFiles\_gput:n.)

This pushes out the other names trees (but not with dvips). TODO: currently it simply write in the root of the name tree. That is the fastest. If they get longer we perhaps need to build something with Kids and Limits.

\\_\_pdfmanagement\_/Catalog/Names/?\_gpush:

```

668 \cs_new_protected:cpn { __pdfmanagement_/Catalog/Names_gpush:n } #1 % #1 name of name tree
669 {
670   \pdfdict_if_empty:nF { g__pdf_Core/Catalog/Names/#1 }
671   {
672     \seq_clear:N \l__pdfmanagement_tmpa_seq
673     \prop_map_inline:cn
674       { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/Names/#1 }}
675       { \seq_put_right:Nn \l__pdfmanagement_tmpa_seq {##1~##2}}
676     \seq_sort:Nn \l__pdfmanagement_tmpa_seq
677     {
678       \str_compare:nNnTF {##1} > {##2}
679       { \sort_return_swapped: }
680       { \sort_return_same: }
681     }
682     \exp_args:Nne \__pdf_backend_Names_gpush:nn
683     {#1}
684     {
685       \seq_use:Nn \l__pdfmanagement_tmpa_seq {~}
686     }
687   }
688 }

```

(End of definition for \\_\_pdfmanagement\_/Catalog/Names/?\_gpush:.)

\_\_pdfmanagement\_handler/Catalog/?\_show:

A handler to show the catalog.

```

689 \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/?_show:}

```

```

690 {
691   \iow_term:e
692   {
693     \iow_newline:
694     The~Catalog~contains~in~the~top~level~the~single~value~entries
695     \prop_map_function:cN
696     { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog }}
697     \msg_show_item:nn
698   }
699   \clist_map_inline:Nn \c__pdfmanagement_Catalog_seq_clist
700   {
701     \seq_if_empty:cF { g__pdfmanagement_/Catalog/##1_seq }
702     {
703       \iow_term:e
704       {
705         The~'##1'~array~contains~the~entries
706         \seq_map_function:cN { g__pdfmanagement_/Catalog/##1_seq } \msg_show_item:n
707       }
708     }
709   }
710   \clist_map_inline:Nn \c__pdfmanagement_Catalog_sub_clist
711   {
712     \prop_if_empty:cF { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/##1 } }
713     {
714       \iow_term:e
715       {
716         The~Catalog~subdirectory~'##1'~contains~the~single~value~entries
717         \prop_map_function:cN
718         { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/##1 }}
719         \msg_show_item:nn
720       }
721     }
722   }
723   \tl_show:e {\tl_to_str:n{\pdfmanagement_show:n{Catalog}}}
724 }

```

(End of definition for \_\_pdfmanagement\_handler/Catalog/?\_show:.)

## 2.7 xform / Properties

```

725 \pdfdict_new:n { g__pdf_Core/Xform/Resources/Properties}

```

```

726 \</package>

```

# Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

## Symbols

## B

bool commands:

\\ ..... 27, 36      \bool\_gset\_true:N ..... 43

\bool_new:N	42	\g__kernel_pdfmanagement_- lastpage_shipout_code_tl	72
C			
\clearpage	12	\g__kernel_pdfmanagement_- thispage_shipout_code_tl	71, 74
clist commands:			
\clist_const:Nn	275, 310, 332, 349, 360	\g__kernel_pdfmanagement_- thispage_shipout_code_- tl_	
\clist_map_inline:Nn	283, 343, 370, 402, 441, 699, 710	lastpage_shipout_code_- tl_	
cs commands:			
\cs_generate_variant:Nn	69, 120	end_run_code_tl	71
\cs_if_exist:NTF	97, 101, 135, 139, 172	M	
\cs_new:Npn	642	msg commands:	
\cs_new_protected:Npn	53, 88, 122, 131, 155, 170, 194, 198, 202, 212, 224, 233, 248, 253, 259, 265, 270, 289, 294, 299, 304, 373, 379, 385, 405, 413, 422, 446, 463, 527, 544, 562, 590, 607, 624, 657, 668, 689	\msg_error:nnn	65, 114, 151, 165, 209, 219
\cs_set_eq:NN	51, 70	\msg_error:nnnn	393
E			
exp commands:			
\exp_args:Ne	237, 665	\msg_new:nnn	8, 11, 14, 17, 20, 23, 30, 34
\exp_args:Nne	105, 124, 143, 159, 455, 536, 553, 584, 599, 616, 633, 660, 682	\msg_none:nnn	92
\exp_args:Nnne	471, 483, 495, 507, 519	\msg_show:nnnnnn	200
\exp_args:Nno	408, 416	\msg_show_item:n	706
\exp_args:No	419	\msg_show_item:nn	184, 697, 719
\exp_args:NV	76, 77	\msg_warning:nnn	267, 272
N			
\newpage 5			
P			
pdf commands:			
		\pdf_object_new:n	451, 467, 479, 491, 503, 515, 532, 549, 572, 595, 612, 629
		\pdf_object_ref:n	459, 475, 487, 499, 511, 523, 540, 557, 587, 603, 620, 637
		\pdf_object_write:nnn	452, 468, 480, 492, 504, 516, 533, 550, 574, 596, 613, 630
		\pdf_string_from_unicode:nnN	407, 415
pdf internal commands:			
		\__pdf_backend_catalog_gput:nn	438, 456, 537, 554, 585, 600, 617, 634
		\g__pdf_backend_end_run_tl	16
		\__pdf_backend_info_gput:nn	228
		\__pdf_backend_Names_gpunch:nn	682
		\__pdf_backend_NamesEmbeddedFiles_- add:nn	420, 666
		\__pdf_backend_Page_gput:nn	250
		\__pdf_backend_Page_gremove:n	255
		\__pdf_backend_PageResources_- gpunch:n	77
		\__pdf_backend_PageResources_- gput:nnn	291, 296, 301, 306
		\__pdf_backend_PageResources_- obj_gpunch:	82
		\__pdf_backend_Pages_primitive:n	237
		\__pdf_backend_ThisPage_gpunch:n	76

\\_\_pdf\_backend\_ThisPage\_gput:nn 262  
 \pdfcatalog ..... 1, 2  
 pdfdict commands:  
   \pdfdict\_if\_empty:nTF ..... 235, 670  
   \pdfdict\_if\_exist:nTF .....  
     ..... 55, 95, 133, 157, 204, 214  
   \pdfdict\_new:n ..... 222, 231, 244,  
     245, 285, 308, 345, 404, 412, 655, 725  
   \pdfdict\_use:n .....  
     ..... 239, 454, 494, 506, 518, 552, 632  
 \pdfinfo ..... 1, 2  
 pdfmanagement commands:  
   pdfmanagement:Info ..... 4  
   pdfmanagement:Page ..... 5  
   pdfmanagement:Page/Resources/ColorSpace  
     ..... 6  
   pdfmanagement:Page/Resources/ExtGState  
     ..... 6  
   pdfmanagement:Page/Resources/Pattern  
     ..... 6  
   pdfmanagement:Page/Resources/Shading  
     ..... 6  
   pdfmanagement:Pages ..... 5  
   pdfmanagement:ThisPage ..... 5  
   \pdfmanagement\_add:nnn 3-6, 53, 69, 70  
   \pdfmanagement\_get:nnN ..... 212  
   \pdfmanagement\_if\_active: ..... 49  
   \pdfmanagement\_if\_active:TF ..... 2  
   \pdfmanagement\_if\_active\_p: ..... 2  
   \pdfmanagement\_remove:nn .. 3, 5, 202  
   \pdfmanagement\_show:n .. 3, 5, 198, 723  
 pdfmanagement internal commands:  
   \\_\_pdfmanagement\_/Catalog/AA\_-  
     gpush: ..... 446  
   \\_\_pdfmanagement\_/Catalog/AcroForm\_-  
     gpush: ..... 463  
   \\_\_pdfmanagement\_/Catalog/AF\_-  
     gpush: ..... 527  
   \\_\_pdfmanagement\_/Catalog/MarkInfo\_-  
     gpush: ..... 544  
   \\_\_pdfmanagement\_/Catalog/Names/?\_-  
     gpush: ..... 668  
   \\_\_pdfmanagement\_/Catalog/OCProperties\_  
     gpush: ..... 561  
   \\_\_pdfmanagement\_/Catalog/OutputIntents\_  
     gpush: ..... 590  
   \\_\_pdfmanagement\_/Catalog/Requirements\_  
     gpush: ..... 607  
   \\_\_pdfmanagement\_/Catalog/ViewerPreferences\_  
     gpush: ..... 624  
   \g\_\_pdfmanagement\_active\_bool ... 42  
   \\_\_pdfmanagement\_Catalog\_gpush:  
     ..... 85, 422, 422  
   \c\_\_pdfmanagement\_Catalog\_-  
     nametree\_clist ..... 360, 402, 441  
   \c\_\_pdfmanagement\_Catalog\_seq\_-  
     clist ..... 308, 349, 370, 699  
   \c\_\_pdfmanagement\_Catalog\_sub\_-  
     clist ..... 308, 332, 343, 710  
   \c\_\_pdfmanagement\_Catalog\_-  
     toplevel\_clist ..... 308, 310  
   \\_\_pdfmanagement\_catalog\_XX\_-  
     gput:n ..... 308  
   \g\_\_pdfmanagement\_EmbeddedFiles\_-  
     int ... 641, 646, 648, 650, 652, 659  
   \\_\_pdfmanagement\_EmbeddedFiles\_-  
     name: ..... 642, 642, 663, 666  
   \\_\_pdfmanagement\_get:nnN 87, 122, 216  
   \\_\_pdfmanagement\_gremove:nn . 87, 155  
   \_\_pdfmanagement\_handler/Catalog/?\_-  
     show: ..... 689  
   \\_\_pdfmanagement\_handler/Catalog/Names/EmbeddedFile  
     gput:n ..... 655  
   \\_\_pdfmanagement\_handler\_-  
     gput:nnn ... 13, 61, 87, 88, 120, 520  
   \\_\_pdfmanagement\_handler\_-  
     gremove:nn ..... 131, 206  
   \\_\_pdfmanagement\_if\_active: .. 44, 49  
   \\_\_pdfmanagement\_Info\_gpush: ...  
     ..... 15, 84, 223, 224  
   \\_\_pdfmanagement\_nametree\_add\_-  
     aux:nnn ..... 385, 409, 417  
   \c\_\_pdfmanagement\_PageResources\_-  
     clist ..... 275, 283  
   \\_\_pdfmanagement\_Pages\_gpush: ..  
     ..... 83, 232, 233  
   \\_\_pdfmanagement\_show:n .... 87, 194  
   \\_\_pdfmanagement\_show:Nn .. 170, 200  
   \l\_\_pdfmanagement\_tmpa\_seq .....  
     ..... 39, 672, 675, 676, 685  
   \l\_\_pdfmanagement\_tmpa\_tl .....  
     . 39, 407, 409, 415, 418, 420, 573, 577  
   \l\_\_pdfmanagement\_tmpb\_tl .. 39, 391  
   \PDFManagementAdd ..... 3, 70  
 pdfmeta commands:  
   \pdfmeta\_standard\_verify:nTF ... 428  
   \pdfpageattr ..... 1, 2, 5  
   \pdfpageheight ..... 5  
   \pdfpageresources ..... 1, 2, 6  
   \pdfpagesattr ..... 1, 2, 5  
 prg commands:  
   \prg\_new\_conditional:Npnn ..... 44  
   \prg\_return\_true: ..... 46  
   \prg\_set\_eq\_conditional:NNn ..... 48  
   \prop ..... 472, 484, 496, 508  
 prop commands:  
   \prop\_gc clear:N ..... 229

\prop_get:NnN	125	\seq_use:Nn	470, 482, 535, 576, 581, 598, 615, 685
\prop_get:NnNTF	388	shipout commands:	
\prop_gput:Nnn	106, 261, 396, 472, 484, 496, 508, 661	\g_shipout_readonly_int	76, 77
\prop_gremove:Nn	144, 160	sort commands:	
\prop_if_empty:NTF	448, 489, 501, 513, 546, 626, 712	\sort_return_same:	680
\prop_if_exist:NTF	176	\sort_return_swapped:	679
\prop_map_function:NN	182, 226, 436, 695, 717	\special	1
\prop_map_inline:Nn	673	str commands:	
\prop_show:N	196	\str_compare:nNnTF	678
\ProvidesExplPackage	4	\str_convert_pdfname:n	3, 4, 108, 127, 146, 162

## S

seq commands:	
\seq_clear:N	672
\seq_count:N	566, 567
\seq_gpop_left:NN	573
\seq_gput_left:Nn	381
\seq_gput_right:Nn	375
\seq_if_empty:NTF	465, 477, 529, 578, 592, 609, 701
\seq_map_function:NN	706
\seq_new:N	41, 372
\seq_put_right:Nn	675
\seq_sort:Nn	676

## T

tl commands:	
\tl_gset:Nn	74, 80
\tl_if_empty:nTF	26, 90
\tl_new:N	39, 40, 71, 72, 73
\tl_show:n	723
\tl_to_str:n	180, 723

## U

use commands:	
\use:N	99, 103, 137, 141, 174, 424, 425, 426, 427, 430, 432, 433, 434, 440, 443
\use_i:nn	51